

Claims:

1. (Currently Amended) A reamer for use in extracting juice from citrus

5 comprising:

a plurality of primary ribs for contacting the citrus;

wherein ~~a~~the plurality of primary ribs each have ~~at least two different~~
separate convex profiles, being an upper profile and a lower profile;

10 a concave transitional section located between the upper and the lower
~~profiles~~profile.

2. (Currently Amended) The reamer of claim 1 wherein:

the concave transitional section ~~smoothly~~smoothly blends the upper
and lower profiles together.

15

3. (Previously Amended) The reamer of claim 1 wherein:

the upper profile has a larger longitudinal radius or sharper apex angle
than the lower profile.

20 4. (Previously Amended) The reamer of claim 1, further comprising:

a plurality of secondary ribs that are lower than the primary ribs.

5. (Original) The reamer of claim 1 wherein:

the primary ribs are blade like.

25

6. (Previously Amended) The reamer of claim 1 wherein:
the top of at least some of the primary ribs form spikes to hold fruit in
place.

5 7. (Previously Amended) The reamer of claim 4 wherein:
the secondary ribs are located between the the primary ribs.

8. (Previously Amended) The reamer of claim 1 wherein:
the reamer includes at least one paddle- near a base of the primary ribs
10 for removing pulp.

9. (Original) A citrus press comprising:
a reamer;
a housing to support the reamer;
15 a motor to drive the reamer, said motor contained in the housing; and
a fruit dome carried by an actuating arm;
wherein the fruit dome has a trajectory determined by the actuating
arm, the trajectory having a curved portion and a generally linear
portion that is generally coincident with an axis of rotation of the
20 reamer.

10. (Original) The citrus press of claim 9 wherein:
the actuating arm co-operates with a micro switch lock-out to prevent
early rotation of the juicing reamer.

25

11. (Original) The reamer of claim 9 wherein:
the reamer has an apex on which is formed a central spike which co-
operates with an internal surface of the fruit dome to limit the gap
between the reamer and the dome.

5

12. (Original) The citrus press of claim 11 wherein:
the fruit dome includes a profile on its inner surface that corresponds
with the profile of the reamer profile.

- 10 13. (Original) The citrus press of claim 9 wherein:
the fruit dome is removable for washing.

14. (Original) The citrus press of claim 9 wherein:
the fruit dome includes a stub shaft for attaching the dome to a
15 corresponding aperture in the actuating arm.

15. (Original) The citrus press of claim 9 wherein:
the fruit dome includes one or more internal edges to grip the skin of
the fruit.

20

16. (Currently Amended) The citrus press of claim 9, further comprising
wherein;
~~the a~~ juice collector that includes a sealable spout to control ~~the a~~ flow
of juice from the collector.

25

17. (Original) A citrus press comprising:

a reamer;

a housing to support the reamer;

5 a motor to drive the reamer, said motor contained in the housing; and

a fruit dome carried by an actuating arm;

wherein the actuating arm has a four bar linkage hinge with at least one
fixed pivot attached to the housing.

10 18. (Original) The citrus juicer of claim 17 wherein:

the actuating arm is a collapsible quadrilateral hinge.

19. (Original) The citrus juicer of claim 17 wherein:

the actuating arm co-operates with a micro switch lock-out to prevent

15 early rotation of the juicing reamer.

20. (Original) The reamer of claim 17 wherein:

the reamer has an apex on which is formed a central spike which co-

operates with an internal surface of the fruit dome to limit the gap

20 between the reamer and the dome.

21. (Original) The citrus juicer of claim 17 wherein:

the fruit dome includes a profile on its inner surface that corresponds

with the profile of the reamer profile.

25

22. (Original) The citrus juicer of claim 17 wherein:

the fruit dome is removable for washing.

5 23. (Original) The citrus juicer of claim 17 wherein:

the fruit dome includes a stub shaft for attaching the dome to a
corresponding aperture in the actuating arm.

24. (Original) The citrus juicer of claim 17 wherein:

10 the fruit dome includes one or more internal edges to grip the skin of
the fruit.

25. (Currently Amended) The citrus juicer of claim 17, ~~wherein~~ further
comprising:

15 ~~the a~~ juice collector that includes a sealable spout to control ~~the a~~ flow
of juice from the collector.

26. (Previously Amended) A spout for limiting the flow of fluid from a
container, comprising:

20 a spout that is hinged to the container;

the spout supporting an elastomeric plug;

an aperture in the container;

wherein the elastomeric plug fits into the aperture in the container to
stop a flow of fluid therethrough;

the plug having a portion that is larger than the aperture, that portion preventing the plug from dislodging under an influence of gravity.

27. (Original) The spout of claim 26 wherein:

5 the portion is an enlarged head.